



RUBIFIN N°4

Universal solvent for rapid removal of oils, rosin, paraffin, zapon, protective varnish, decorative varnish, in ultrasonic processes.

COMPATIBILITY:

- All metals

INGREDIENTS:

- Solvents

PHYSICAL AND CHEMICAL DATA:

- pH concentrated: n.m
- Density: 0.927
- Flash point: 71°C/ 21°F
- Surface tension: 29.2 mN/m

INSTRUCTIONS FOR USE:

- Concentration: 100%
- Temperature: 20 to 50°C (68 to 122°F)
- Time: 3 to 10 minutes

Work in a naturally ventilated place or one equipped with an aspiration system

PROCESS EXAMPLE:

- Removes oils on all types of parts (with blind holes)

CLEANING

RUBIFIN N°4	TAP WATER RINSE	DI WATER RINSE	HOT AIR DRYING
Conc.: 100% Temp.: 30 à 50°C 86 à 122°F Time: 3-5 min	Temp.: 20°C 68°F Time: 2 min	Temp.: 20°C 68°F Time: 2 min	

US

BENEFITS:

- Substitution of acetone, methylene chloride and NEP
- VOC free
- High flash point
- Easily removed with detergent

12/07/21

STORAGE CONDITIONS:

- Keep the recipient hermetically sealed between 5°C and 40°C (41°F and 104°F) in a dry place.
- Always keep in packaging made from the same material as the original packaging.



If you have any questions, please contact our Application Centre on: +41 22 365 46 66

