



DECOCLEAN 508

VOC-free detergent, for spray cleaning application.

COMPATIBILITY:

- All metals

Not compatible: carbides

INGREDIENTS:

- Surfactants
- Chelating agents
- Corrosion inhibitors

PHYSICAL AND CHEMICAL DATA:

- pH value: 9.0
- Density: 1.031
- Surface tension: 30.8 mN/m

INSTRUCTIONS FOR USE:

Decoclean 508 gives good performance at 5% concentration in tap water. In case of larger amounts of oil or grease, product concentration may be increased to 7%

- Concentration: 5 to 7%
- Temperature: 20 to 50°C (68 à 122°F)
- Time: 2 to 4 min.

Use: dipping, with or without ultrasonic, finishing with compressed air or warm air drying.

DEGREASING FOUNTAIN NGL FD 60:

Designed for the following industries: watchmaking, medical, electronics, micromechanics and aeronautics...

Offers an alternative to traditional solutions using solvents, oils or alcohols, which are harmful to health and the environment.

BENEFITS:

- Substitution of kerosene and solvents
- Designed for aqueous solutions
- Reduced operating costs
- Improved safety/environmentally safe
- Maintenance of the degreasing solution through an oil separator
- Improved cleanliness and organisation of workshops
- Mobile equipment

BENEFITS:

- Alternative to kerosene, for use in degreasing fountain NGL FD60
- Does not contain VOCs
- Works at room temperature
- Compatible with all metals except carbides
- Efficiently releases oils

STORAGE CONDITIONS:

- Keep the recipient hermetically sealed between 5°C and 40°C (41°F and 104°F) in a dry place.
- Always keep in packaging made from the same material as the original packaging.



22/12/17



If you have any questions, please contact our Application Centre on: +41 22 365 46 66

NGL CLEANING TECHNOLOGY SA - ECOLOGICAL CLEANING SOLUTIONS

Chemin de la Vuarpillière 7 // CH-1260 NYON // SWITZERLAND
+41 22 365 46 66 // contact@ngl-group.com // www.ngl-group.com




**SWISS
QUALITY**

