



NANOCLEAN 100

Liquid alkaline detergent for the removal of oils in ultrasonic or spray cleaning processes.

COMPATIBILITY:

- Titanium
- Steels
- Nitinol
- Ceramics, plastics

INGREDIENTS:

- Surfactants, phosphates
- Chelating agents, solubilizing agents

PHYSICAL AND CHEMICAL DATA:

- pH concentrated: 7.9
- pH (1%): 8.8
- Density: 1.370
- Surface tension: 32.4 mN/m

INSTRUCTIONS FOR USE:

Optimum use conditions may be affected by the quality of the water used in the baths, as well as the type and quantity of contaminants.

- Concentration: 3 to 8%
- Temperature: 30 to 55°C
- Time: 3 to 5 minutes

FOR USE IN THE NGL FD60 DEGREASING FOUNTAIN:

Degreasing fountain intended for several types of industries: watchmaking, medical, electronics, micromechanics and aeronautics...

It replaces traditional solutions that use solvents, oils or alcohols, which are harmful to health and the environment.

BENEFITS:

- Substitute for kerosene and solvents
- Water based solution
- Reduced operating costs
- Improved safety/environmentally safe
- Recycling of the degreasing solution
- Improved cleanliness and organisation of workshops
- Mobile equipment

BENEFITS:

- Replaces advantageously solvents classified as VOC
- Rapid and effective oil separation
- Validated in medical processes
- Does not leave any film on the surface
- Product does not attack metals

STORAGE CONDITIONS:

- Keep the recipient hermetically sealed between 5°C and 40°C (41°F and 104°F) in a dry place.
- Always keep in packaging made from the same material as the original packaging.



19/02/18



If you have any questions, please contact our Application Centre on: +41 22 365 46 66

NGL CLEANING TECHNOLOGY SA - ECOLOGICAL CLEANING SOLUTIONS

Chemin de la Vuarpillièrè 7 // CH-1260 NYON // SWITZERLAND
+41 22 365 46 66 // contact@ngl-group.com // www.ngl-group.com




**SWISS
QUALITY**

