



SCHUTZLACK 2005 SP L ROSE

Surface protection lacquer against shocks and scratches, during storage operations.

COMPATIBILITY:

- All metals
- Mineral lenses
- Organic lenses excepted polycarbonate

INGREDIENTS:

- Isopropanol, acetone
- Polymers, dye

PHYSICAL AND CHEMICAL DATA:

- Not watersoluble
- Color: pink
- Density: 0,815
- %sec: 9.0 - 10.3
- Viscosity: 4-5 cP
- Flash point: < 21°C (69,80°F)

INSTRUCTIONS FOR USE:

Use 100%: room temperature

Use of the lacquer:

▪ Spraygun


Spray the surface which needs protection from a distance of 10-20 cm, leave the lacquer dry for 5-10 min, depending on the layer amount.

▪ Dipping or paintbrush

PROCESSES EXAMPLES FOR ELIMINATION OF THE LACQUER


▪ Schutzlack removal from stainless steel

CLEANING



▪ Schutzlack removal from copper and sensitive steels

CLEANING



BENEFITS:

- Dries rapidly, leaving an even protection layer
- Protects against shocks and scratches
- Can be used as a varnish masking for polishing steps
- Removable with aqueous detergent (see processes below)

01/04/21

STORAGE CONDITIONS:

- Protect from sunlight and do not expose to temperatures exceeding 50°C (122°F). Keep well away from all sources of ignition.
- The shelf life of the product is 24 months from the date of manufacture, under the appropriate storage conditions.



If you have any questions, please contact our Application Centre on: +41 22 365 46 66

