



SCHUTZLACK 2005 SP L ROSE

Surface protection lacquer against shocks and scratches, during storage operations.

COMPATIBILITY

- All metals
- Mineral lenses
- Organic lenses excepted polycarbonate

INGREDIENTS

- Isopropanol, acetone
- Polymers, dye

PHYSICAL AND CHEMICAL DATA

- Not watersoluble
- Color: pink
- Density: 0,815
- %sec: 9.0 - 10.3
- Viscosity: 4-5 cP
- Flash point: 11°C (51,8°F)

INSTRUCTIONS FOR USE

Use 100%: room temperature

Use of the lacquer:

- Spraygun


Spray the surface which needs protection from a distance of 10-20 cm, leave the lacquer dry for 5-10 min, depending on the layer amount.

- Dipping or paintbrush

PROCESSES EXAMPLES FOR ELIMINATION OF THE LACQUER


- Schutzlack removal from stainless steel

CLEANING



- n Schutzlack removal from copper and sensitive steels

CLEANING



BENEFITS

- Dries rapidly, leaving an even protection layer
- Protects against shocks and scratches
- Can be used as a varnish masking for polishing steps
- Removable with aqueous detergent (see processes below)

21/05/21

STORAGE CONDITIONS

- Protect from sunlight and do not expose to temperatures exceeding 50°C (122°F). Keep well away from all sources of ignition.
- The shelf life of the product is 24 months from the date of manufacture, under the appropriate storage conditions.



If you have any questions, please contact our Application Centre on: +41 22 365 46 66

NGL CLEANING TECHNOLOGY SA - ECOLOGICAL CLEANING SOLUTIONS

Chemin de la Vuarpillière 7 // CH-1260 NYON // SWITZERLAND
+41 22 365 46 66 // contact@ngl-group.com // www.ngl-group.com

