



# SCHUTZLACK NGL BLEUE

Protective lacquer surfaces against shocks and scratches, during storage operations.

## COMPATIBILITY:

- All metals
- Mineral lenses
- Organic lenses excepted polycarbonate

## INGREDIENTS:

- Ethanol

## PHYSICAL AND CHEMICAL DATA:

- Not watersoluble
- Color: blue
- Density: 0,884
- %sec: 6,0
- Viscosity: 16 cP
- Flash point: 20°C (68°F)

## INSTRUCTIONS FOR USE:

Use 100%: room temperature

### ▪ Spraygun

Spray the surface which needs protection from a distance of 10-20 cm, leave the lacquer dry for 5-10 min, depending on the layer amount.

### ▪ Dipping or paintbrush

## PROCESSES EXAMPLES FOR ELIMINATION OF THE LACQUER

### ▪ Schutzlack removal from stainless steel

#### CLEANING



### ▪ Schutzlack removal from copper

#### CLEANING



## BENEFITS:

- Protects against shocks and scratches
- Resistant to modified alcohol solvents such as DOWCLEN 1601
- Can be used as a varnish masking for polishing steps
- Dries rapidly
- Uniform protective layer
- Removable with aqueous detergent

12/07/21

## STORAGE CONDITIONS:

- Protect from sunlight and do not expose to temperatures exceeding 50°C (122°F). Keep well away from all sources of ignition.
- The shelf life of the product is 24 months from the date of manufacture, under the appropriate storage conditions.



If you have any questions, please contact our Application Centre on: +41 22 365 46 66

## NGL CLEANING TECHNOLOGY SA - ECOLOGICAL CLEANING SOLUTIONS

Chemin de la Vuarpillière 7 // CH-1260 NYON // SWITZERLAND  
+41 22 365 46 66 // contact@ngl-group.com // www.ngl-group.com



 SWISS QUALITY

