



SCHUTZLACK NGL BLEUE

Protective lacquer surfaces against shocks and scratches, during storage operations.

COMPATIBILITY:

- All metals
- Mineral lenses
- Organic lenses excepted polycarbonate

INGREDIENTS:

- Ethanol

PHYSICAL AND CHEMICAL DATA:

- Not watersoluble
- Color: blue
- Density: 0,884
- %sec: 6,0
- Viscosity: 16 cP
- Flash point: 20°C (68°F)

INSTRUCTIONS FOR USE:

Use 100%: room temperature

▪ Spraygun


Spray the surface which needs protection from a distance of 10-20 cm, leave the lacquer dry for 5-10 min, depending on the layer amount.

▪ Dipping or paintbrush

PROCESSES EXAMPLES FOR ELIMINATION OF THE LACQUER


▪ Schutzlack removal from stainless steel

CLEANING



▪ Schutzlack removal from copper

CLEANING



BENEFITS:

- Protects against shocks and scratches
- Resistant to modified alcohol solvents such as DOWCLENE 1601
- Can be used as a varnish masking for polishing steps
- Dries rapidly
- Uniform protective layer
- Removable with aqueous detergent

01/04/21

STORAGE CONDITIONS:

- Protect from sunlight and do not expose to temperatures exceeding 50°C (122°F). Keep well away from all sources of ignition.
- The shelf life of the product is 24 months from the date of manufacture, under the appropriate storage conditions.



If you have any questions, please contact our Application Centre on: +41 22 365 46 66

NGL CLEANING TECHNOLOGY SA - ECOLOGICAL CLEANING SOLUTIONS

Chemin de la Vuarpillière 7 // CH-1260 NYON // SWITZERLAND
+41 22 365 46 66 // contact@ngl-group.com // www.ngl-group.com

