



MESSERCLEAN

Liquid product for oil and polishing paste removal.

COMPATIBILITY:

- Steel
- Stainless steel
- Hard metal
- Silicon
- Ceramics

INGREDIENTS:

- Organic acid, surfactants, phosphates
- Chelating agents, anti-corrosion agents

PHYSICAL AND CHEMICAL DATA:

- pH concentrated: 0.20
- pH (1%): 2.1
- Density: 1.070
- Surface tension: 28.4 mN/m

INSTRUCTIONS FOR USE:

Optimum use conditions may be affected by the quality of the water used in the baths, as well as the type and quantity of contaminants.

- Concentration: 3 to 10%
- Temperature: 35 to 60°C (95 to 140°F)
- Time: 30 sec. to 5 minutes

PROCESS EXAMPLE:

CLEANING

MESSERCLEAN	GALVEX 20.01	TAP WATER RINSE	DI WATER RINSE	HOT AIR DRYING
Conc.: 3% Temp.: 55°C 131°F Time: 5 min	Conc.: 3% Temp.: 60°C 140°F Time: 5 min	Temp.: 20-30°C 68-86°F Time: 3-5 min	Temp.: 20-30°C 68-86°F Time: 3-5 min	
US	US			

BENEFITS:

- Removes rapidly all contaminants
- Leaves no residues after drying
- Excellent for the cleaning of ceramics, hard metal and silicon

22/01/21

STORAGE CONDITIONS:

- Keep the recipient hermetically sealed between 5°C and 40°C (41°F and 104°F) in a dry place.
- Always keep in packaging made from the same material as the original packaging.



If you have any questions, please contact our Application Centre on: +41 22 365 46 66

NGL CLEANING TECHNOLOGY SA - ECOLOGICAL CLEANING SOLUTIONS

Chemin de la Vuarpillière 7 // CH-1260 NYON // SWITZERLAND
+41 22 365 46 66 // contact@ngl-group.com // www.ngl-group.com




**SWISS
QUALITY**

