

HELIT 2022

Neutral universal detergent with a hydrophilic superfinish on the surface in ultrasonic processes prior to drying.

LUXURY ACCESSORIES RANGE

FUNCTION	APPLICATION/POLLUTION	
Hydrophilic superfinish	Light pollutions	HYDROPHILIC FINISH
COMPATIBILITY Stainless steel 	 ABS 	Water θ Substrate Hydrophobic surface
 Brass (leaded and unleaded) Rhodium, palladium Gold: white, pink, yellow 	AluminiumNickel silver	Reduction of the surface tension of water by surfactants
COMPONENTS Surfactants		θ

- No NTA, phosphates, or DEA
- No CMR compounds, REACH compliant

PHYSICOCHEMICAL DATA

- pH concentrated: 7.1
- Density: 1.04
- Surface tension: 28.2 mN/m

• Keep the container hermetically sealed between 5°C and 40°C (41°F and 104°F) in a dry place.

STORAGE CONDITIONS

 Always keep in packaging made from the same material as the original packaging (HDPE).

INSTRUCTIONS FOR USE*

- Concentration: 1 to 3%
- Temperature: 50 to 60°C (122 to 140°F)
- Time: 2 to 4 minutes

*Dependent on the quality of water and the nature and quantity of contaminants.

PROCESS EXAMPLE



If you have any questions, please contact our Application Centre on: +41 22 365 46 66

NGL CLEANING TECHNOLOGY SA - ECOLOGICAL CLEANING SOLUTIONS Chemin de la Vuarpillière 7 - CH-1260 NYON - SWITZERLAND +41 22 365 46 66 - contact@ngl-group.com - www.ngl-group.com





22/11/22

Hydrophilic finish