



ALLSTRIP

Universal solvent with a high flash point for the removal of glues, waxes, lacquers, setters cement, in ultrasonic process or in beakers.



JEWELLERY RANGE

FUNCTION	APPLICATION/POLLUTION
Ultrasonic cleaning	Removal of setters cement, waxes, glues and lacquers

COMPATIBILITY

- Stainless steel
 - Lead-free brass
 - Silver: 800 - 925 (sterling)
 - Gold: white, pink, yellow
 - Platinum
 - Rhodium, palladium
 - Stones*:
 - Diamond, sapphire, ruby, emerald
 - Zirconium, ceramic
- *Please contact NGL before implementing a process

COMPONENTS

- REACH compliant

PHYSICOCHEMICAL DATA

- pH concentrated: n.m.
- Density: 0.99
- Flash point: 88°C (190°F)

INSTRUCTIONS FOR USE*

- Concentration: 100%
- Temperature: 20 to 50°C (68 to 122°F) (not exceed 70°C / 158°F)
- Time: 2 to 10 minutes



*Use in a space that is naturally ventilated or equipped with an aspiration. system.

PROCESS EXAMPLES

- Removal of glues, waxes, lacquers, setters cement, in beakers



- Removal of contaminants in ultrasonic process



30/08/23

STORAGE CONDITIONS

- Keep the recipient hermetically sealed between 5°C and 40°C (41°F and 104°F) in a dry place.
- Always keep in packaging made from the same material as the original packaging (HDPE).



If you have any questions, please contact our Application Centre on: +41 22 365 46 66

