

DECOSPRAY TM

Light alkaline product for the removal of neat oil in spray or ultrasonic processes. Requires an oil separator.



FUNCTION	APPLICATION/POLLUTION
Oil removal in spray or ultrasonic processes with an oil separator	Neat oils

COMPATIBILITY

- Stainless steel and tempered Copper alloys:
- Aluminium BrassGold: white, pink, yellow CuBe
- Rhodium, palladium Nickel silver

COMPONENTS

- Surfactants, chelating agents
- No CMR compounds, REACH compliant

PHYSICOCHEMICAL DATA

■ pH concentrated: 9.6

■ Density: 1.12


Surface tension: 39.7 mN/m

INSTRUCTIONS FOR USE*

Concentration: 2 to 5%

■ Temperature: 40 to 70°C (104°F to 158°F)

■ Time: 3 to 5 minutes



STORAGE CONDITIONS

- Keep the recipient hermetically sealed between 5°C and 40°C (41°F and 104°F) in a dry place.
- Always keep in packaging made from the same material as the original packaging (HDPE).

PROCESS EXAMPLES

Interoperation cleaning

CLEANING



Final cleaning

CLEANING





If you have any questions, please contact our Application Centre on: +41 22 365 46 66





^{*}Dependent on the quality of the water and the nature and quantity of contaminants.