

GALVEX 20.02

Universal detergent for the removal of polishing pastes, soluble oil and light pollutions in an ultrasonic process.

WATCH INDUSTRY

FUNCTION	APPLICATION/POLLUTION
Ultrasonic cleaning, interoperation, surface preparation	Soluble oils, polishing pastes, tumbling residues, etc.

COMPATIBILITY

- Stainless steel
- Gold: white, pink, yellow
- Rhodium, palladium
- Copper alloys:
 - CuBe
 - Nickel silver

COMPONENTS

- Surfactants, solubilising agent
- No NTA, phosphates, DEA
- No CMR compound, REACH compliant

PHYSICOCHEMICAL DATA

pH concentrated: 10

■ Density: 1.03

Surface tension: 27.6 mN/m

INSTRUCTIONS FOR USE*

Concentration: 2 to 5%Temperature: 40 to 70°C

■ Time: 3 to 5 minutes

Cavitation bubbles Substrate Parameters for cleaning: Clean and bright surface. Cleaned blind holes.

STORAGE CONDITIONS

- Keep the recipient hermetically sealed between 5°C and 40°C (41°F and 104°F) in a dry place.
- Always keep in packaging made from the same material as the original packaging (HDPE).

PROCESS EXAMPLES

Cleaning after polishing

CLEANING



• Final cleaning and brightening

CLEANING

GALV	EX 20.02
	Tap water 2-5% 40-70°C 104-158°F 3-5 min
	US

TAP WATER RINSE

Temp.: 20-30°C 68-86°F Time: 2-3 min RODASTEL 30

Tap water
Conc.: 3-5%
Temp.: 30-60°C
Time: 2-3 min
US

TAP WATER RINSE

Temp.: 20-30°C 68-86°F Time: 1-2 min DI WATER RINSE

Temp.: 20-30°C 68-86°F Time: 1-2 min DI WATER RINSE Temp.: 20-30°C

Time: 1-2 min

HOT AIR DRYING

Application Centre

If you have any questions, please contact our Application Centre on: +41 22 365 46 66





19/08/25

^{*}Dependent on the quality of the water and the nature and quantity of contaminants.