

HELIT 2022

Neutral universal detergent with a hydrophilic superfinish on the surface in ultrasonic processes prior to drying.

LUXURY ACCESSORIES RANGE

FUNCTION	APPLICATION/POLLUTION
Hydrophilic superfinish	Light pollutions

COMPATIBILITY

- Stainless steel
- Brass (leaded and unleaded)
- Rhodium, palladium
- Gold: white, pink, yellow
- ABS
- Aluminium
- Nickel silver

COMPONENTS

- Surfactants
- No NTA, phosphates, or DEA
- No CMR compounds, REACH compliant

HYDROPHILIC FINISH Water Hydrophobic surface Reduction of the surface tension of water by surfactants Hydrophilic finish

PHYSICOCHEMICAL DATA

pH concentrated: 7.1

■ Density: 1.04

Surface tension: 28.2 mN/m

STORAGE CONDITIONS

- Keep the container hermetically sealed between 5°C and 40°C (41°F and 104°F) in a dry place.
- Always keep in packaging made from the same material as the original packaging (HDPE).

INSTRUCTIONS FOR USE*

■ Concentration: 1 to 3%

■ Temperature: 50 to 60°C (122 to 140°F)

■ Time: 2 to 4 minutes

*Dependent on the quality of water and the nature and quantity of contaminants.

PROCESS EXAMPLE

• Final cleaning

CLEANING	
GALVEX 20.02	
Tap water	
Conc.: 2-5%	
Temp.: 50-70°C	
122-158°F	
Time: 3-5 min	
US	

TAP WATER Temp.: 20-30°C Time: 2-3 min

FINISHING **HELIT 2022**

US

TAP WATER

Temp.: 20-30°C

DI WATER

Temp.: 20-30°C 69-86°F

DI WATER RINSE

Temp.: 20-30°C Time: 1-2 min

HOT AIR

If you have any questions, please contact our Application Centre on: +41 22 365 46 66



