






NEW BIOLOGICAL PARTS CLEANER



ECOLOGICAL CLEANING SOLUTIONS

SWISS QUALITY

THE BENEFITS OF PARTS CLEANER



THE PROBLEM WITH SOLVENTS

Traditional solvents are still frequently used in workshops and factories to clean various parts, creating risks to the health and safety of operators. These products are toxic through contact or inhalation and flammable.



Toxic

Flammable



They are restrictive when it comes to upgrading facilities and eliminating waste. They are also a source of environmental hazard: accidental spills or release of volatile organic compounds (VOCs).



THE PARTS CLEANER PROCESS

The biological parts cleaner works with a **SoClean Liquid** with a solvent-free, non-toxic and environmentally friendly, pH neutral cleaning solution, heated at 38°C, and **SoClean Tabs**, microorganism tablets which break down oils and continuously regenerate the solution. This process guarantees **effective cleaning**, with no residue on the parts, and helps limit chemical **consumption, maintenance and waste**.

NG



THE BIOLOGICAL PARTS CLEANER 40L The ergonomic design of this cleaner offers various cleaning and filtration systems and a user-friendly control unit.





CLEANING SOLUTION

An aqueous formula made up of specific, non-toxic and non-flammable surfactants that loosen and break down dirt.





A CONCENTRATE OF MICROORGANISMS Biodegradation of dirt, continuous purification of the cleaning bath.





TECHNICAL FEATURES

| Parts washer dimensions | 820 x 530 x 1050 mm |
|--------------------------------|--|
| Cleaning table dimensions | 550 x 430 x 150 mm |
| Empty weight | 23 kg |
| Tank volume | 40 liters |
| Soaking tray | 4 liters / useable dimensions of the tray: 240 x 220 x 80 mm |
| Pump flow | adjustable from 0 to 6 litres/min + low flow tap |
| Heating power | 2 KW |
| Average electrical consumption | 150 W/H |
| Maximum load | 30 kg |
| Mobility | 4 wheels polyurethane, 1 with brake |
| Component | HDPE |
| Tools | Interchangeable brush |
| Filtration | Bag filter polypropylene 50 μm |
| Electrical | 230 V ≈ |



Ergonomic cleaning table



Electromechanical box can be dismantled without tools



Filter socks 50µm



Heating time from 15 to 38°C in 15 min



MOBILE MACHINE Fountain with 4 wheels functioning when hot



ERGONOMIC CLEANING TABLE dip-coating zone







DIP-COATING ZONE Allows you to work as a background task



EASY MAINTENANCE

Electromechanical box interchangeable without tools

DEMONSTRATION:







IN EXTENSION OF RANGE:



NGL CLEANING TECHNOLOGY SA - ECOLOGICAL CLEANING SOLUTIONS Chemin de la Vuarpillière 7 // CH-1260 NYON // SWITZERLAND +41 22 365 46 66 // contact@ngl-group.com // www.ngl-group.com



