

# **UNISON I**

Universal liquid detergent for the removal of polishing pastes, soluble oils and light pollutions in ultrasonic process.



## **JEWELLERY RANGE**

FUNCTION	APPLICATION/POLLUTION
Ultrasonic cleaning. Interoperation, surface preparation.	Soluble oils, polishing pastes, tumbling residues, etc.

### COMPATIBILITY

- Stainless steel
- Lead-free brass
- Silver:
  - 800 925 (sterling)
- Gold: white, pink, yellow
- Platinum

- Rhodium, palladium
- Stones\*:
  - Diamond, sapphire, ruby, emerald
  - Zirconium, ceramic

### **COMPONENTS**

- Surfactants, chelating agents
- No CMR compound, REACH compliant

### PHYSICOCHEMICAL DATA

■ pH concentrated: 10.9

Density: 1.01

Surface tension: 31.0 mN/m

### **INSTRUCTIONS FOR USE\***

Concentration: 2 to 5%
Temperature: 40 to 70°C
Time: 3 to 5 minutes

# Cavitation bubbles Substrate Parameters for cleaning: Clean and bright surface. Cleaned blind holes.

### STORAGE CONDITIONS

- Keep the recipient hermetically sealed between 5°C and 40°C (41°F and 104°F) in a dry place.
- Always keep in packaging made from the same material as the original packaging (HDPE).

### **PROCESS EXAMPLES**

Cleaning after polishing

### **CLEANING**



• Final cleaning and brightening



OLL/ IIIII G	
UNISON I	
Tap water Conc.: 2-5% Temp.: 40-70°C 104-158°F Time: 3-5 min	
US	

TAP WATER RINSE

Temp.: 20-30°C 68-86°F Time: 3-5 min RODASTEL 30

Tap water
Conc.: 3-5%
Temp.: 30-60°C
86-140°F
Time: 2-3 min

TAP WATER RINSE

Temp.: 20-30°C 68-86°F Time: 3-5 min DI WATER RINSE

Temp.: 20-30°C 68-86°F Time: 3-5 min DI WATER RINSE

Temp.: 20-30°C 68-86°F Time: 3-5 min

HOT AIR DRYING

Application Centre

If you have any questions, please contact our Application Centre on: +41 22 365 46 66





11/11/25

<sup>\*</sup>Please contact NGL before implementing

<sup>\*</sup>Dependent on the quality of the water and the nature and quantity of contaminants.